Category	Model Number	Product Photo	Input Voltage	Desciption	Detection	Sensing Type	Maximum Mounting Height	IP Rating	Certification	Compatibility	Comments
					Cor	ntrol Options	: Bluctooth C	ommissionin	4		
Fixture / Zone Controller	PPA104S		120-277VAC	20A Relay Power Pack Bluetooth Commissioning 0-10V Dimming	1	/	/	20	cULus	Any dimmable product.	Must be used together with corresponding Bluetooth Commissioning Controls. Can be controlled using Keilton User Commissioning App
Motion Sensor	EFS104	9	120-277VAC	Side-Mount Sensor Fixture - External Bluetooth Commissioning	Daylight Harvesting + Motion	PIR	40FT	66	cULus		
Wall Switch	WP1013		CR20232x2 Batteries	3-Key Wireless Wall Switch Bluetooth Commissioning	/	/	/	20	cULus		
	WP10135		120-277VAC	3-Key AC Wireless Wall Switch Bluetooth Commissioning	/	/	1	20	cULus		
						Control Opti	ons: Sensors d	& Remotes			
Sensors	EL-ZY-ANT5-4-MS	-	12V-24DC	Plug-In Motion Sensor	Daylight Harvesting + Motion	Bi-Level Microwave	40FT	65	cULus	Round High Bay: Standard Series Linear High Bay: Standard Series	Requires "EL-MS-RC-100" remote to program. See line 16.
	EL-MS-BRI819P-B-O	-	120-277VAC	ON/OFF Motion Sensor	Motion	PIR	25FT	20	cULus	Any dimmable product.	Can be programmed via dipswitches or with "EL-MS-RC-100". See line 16.
	EL-MS-BRI819P-B-D	-	120-277VAC	0-10V Dimming Motion Sesnor	Motion	PIR	25FT	20	cULus		Sensor is mounted externally
	EL-AC-ACC-AMS02	0	12V DC	0-10V Dimming Motion Sesnor	Motion	Bi-Level Microwave	40FT	65	cULus	Round High Bay: High Power Series Round High Bay: Smart Series Linear High Bay: Smart Series Linear Fixture: Tri-Proof Series	Must be used in conjuction with "EL-AC-ACC-A-RM02" remote.
	EL-MS-BRI823	0	120-277VAC	Integrated Sensor - Outdoor Fixture	Daylight Harvesting + Motion	PIR	40FT	66	cULus	Area Light: Standard Series Post Top: Standard Series	Installed internally
Remotes	EL-MS-RC-100	0000 (((((((((((((((((2x AAA Battery	Remote Control for Motion Sensor	Daylight Harvesting + Motion	PIR	Upload: 50FT	/	/	EL-ZY-ANT5-4-MS EL-MS-BRI819P-B-O EL-MS-BRI819P-B-D	Battery not included
	EL-AC-ACC-A-RM02		2x AAA Battery	Remote Control for AMS02 Motion Sensor	Daylight Harvesting + Motion	PIR	Upload: 50FT	/	/	EL-AC-ACC-AMS02 Linear High Bay: Smart Series Round High Bay: Smart Series	Battery not included
Control Options: Photocell											
Photocell	EL-MS-WP-Photocell	THE PARTY OF	120-277VAC	Integranted Standard Photocell	Photocell	/	/	65		Canopy: Standard & Round Series Floodlight: Standard Series Wall Pack: All Series	
Photocell	EL-MS-ACC-SL-Photocell 120-277V		120-277VAC	Integranted Standard Photocell	Photocell	/	/	65		LED Area Lights	
Photocell	EL-MS-ACC-SL-Photocell 480VAC		347-480VAC	Integranted Standard Photocell	Photocell	/	1	65		LED Area Lights	
		·			Dri	ver Options:	Emergency B	attery Backı	р		
Emergency Backup Battery	EL-U-HB-EM	Ç.	100-347VAC	Rugby Version Emergency Battery Backkup Input Power: 15W Output Power: 30W Discharge Time: 90 minutes	/	/	/	65	cULus	Any hanging or pendant mounted fixture	
	EL-ZY-EM-BLD-YT15D	2	100-347VAC	Standard Emergency Backup Battery Input Power: 12W Output Power: 15W Discharge Time: 90 minutes	/	/	/	65	cULus	LED Troffers LED Panels LED Linear High Bays LED Linear Fixtures	Remote Control Test Capatbilites
	EL-ZY-EM-BLD-YT08D	-	100-347VAC	Standard Emergency Backup Battery Input Power: 7W Output Power: 8W Discharge Time: 90 minutes	/	/	/	65	cULus	LED Troffers LED Panels LED Linear High Bays LED Linear Fixtures	