



emium™

emium lighting, see differently

EXTERIOR LIGHTING



Contemporary LED Post Top Fixture

10 Year Warranty

IP66 rated for harsh and wet environments.

Commercial/Architectural Grade LED post top light fixtures for general exterior lighting applications. Ideal for commercial buildings, condominiums, hotels, museums/galleries, retail stores/plazas, restaurants, etc.

A variety of light output levels and color temperatures are available to accommodate any application or personal taste.

IP66 rated, making them impervious to the elements (water, dust, insects, etc.)

FEATURES

Easy and Fast Installation

Uniform light color consistency

60,000+ hour life - More than 20.7 years operating 8 hours a day, based on L70 standards

High-quality shatter-resistant borosilicate glass lens

Durable housing - Constructed of one-piece rust and corrosion proof heavy-duty cast aluminum housing that is polyester powder coated for long durability and sealed to be free of dirt and insects

Building control compatible - Dusk-to-dawn and occupancy sensor compatible additional energy savings and reduced utility costs



for more information email info@emium.com or call 224.735.3435 | www.emium.com

EXTERIOR LIGHTING

Ordering Guide: Post Top Series: Example - EL-RL-PT50W27V50KBP

Fixture Type	Wattage	Voltage	CCT (X,X00) Kelvin	Finish	Photocell
EL-RL-PT					
EL-RL-PT Post Top Series	30W 50W 70W 100W 170W	27V 100-277V	30K 3000K 40K 4000K 50K 5000K 57K 5700K	B - Black W - White	P - 120-277V Photocell Blank - No Photocell

Constructed of one-piece rust and corrosion proof heavy-duty cast aluminum housing that is polyester powder coated for long durability and sealed to be free of dirt and insects

SPECIFICATIONS

Model	EL-RL-PT30W	EL-RL-PT50W	EL-RL-PT70W	EL-RL-PT100W	EL-RL-PT170W
Power	30W	50W	70W	100W	170W
Lumen Output†	3900	6500	9000	13,000	21,250
Input Voltage	100 - 277VAC				
Color Temp	3000K 4000K 5000K 5700K				
Beam Angle	82°				
CRI	>75 Ra				
Beam Angle	120° (Type V)				
Physical	Precision die cast aluminum housing Architectural UV resistant black or white powder coat finish for lasting appearance				
Photocell	Optional				
Operating Temp	-40° to 160° F				
IP Rating	IP66				
Rated Life	> 100,000 hrs.				



Pole Mount
Fits 2-3/8" or 3" Tenons

