



emium™

emium lighting, see differently

EXTERIOR LIGHTING



Contemporary LED Post Top Fixture

5 Year Warranty



FEATURES

- Sleek, contemporary design
- Corrosion proof heavy-duty cast aluminum housing
- Available in 45W, 70W, 87W, 130W.
- Install on poles which top diameter limited to 2-3/8" or 3".
- Suitable for installation heights of 8-20 feet.
- 1-10V dimming and projected over 50,000 hrs life span.
- Operating temperature is -40°C to 45°C (-40°F to 113°F).
- Optional single arm design available.
- UL/cUL wet location and DLC premium qualified.

Commercial/Architectural Grade LED post top light fixtures for general exterior lighting applications.


Ideal for commercial, municipal, residential, and other public campus walkways and parking areas.

Elegant design creates an aesthetically pleasing environment.


Four light output levels and three color temperature options are available to accommodate any application or personal taste.



EPA OF POST TOP

Item	
EPA	0.9696

PHOTOMETRICS



for more information email info@emium.com or call 224.735.3435 | www.emium.com

EXTERIOR LIGHTING

Ordering Guide: Post Top Series: Example - EL-MS-PT70W27V50KDP

Fixture Type	Wattage	Voltage	CCT (X,X00) Kelvin	Finish	Photocell
EL-MS-PT					
EL-MS-PT Post Top Series	45W 70W 87W 130W	27V 100-277V 48V 347-480V (48V only available in 130 watt)	30K 3000K 40K 4000K 50K 5000K	D - Dark Bronze (Standard) (Custom) B - Black W - White	P - 120-277V Photocell M - Motion Sensor D - 1 - 10V Dimming Blank - No Options

Constructed of rust and corrosion proof heavy-duty cast aluminum housing that is polyester powder coated for long durability and sealed to be free of dirt and insects

SPECIFICATIONS

Model	EL-MS-PT45W	EL-MS-PT70W	EL-MS-PT87W	EL-MS-PT130W
Power	45W	70W	87W	130W
Lumen Output @5000K	5500	8500	10,600	15,800
Input Voltage	100 - 277VAC (480VAC driver only available for 130W model)			
Color Temp	3000K 4000K 5000K			
Photometry	General Distribution			
CRI	>75 Ra			
Physical	Precision die cast aluminum housing Architectural UV resistant powder coat finish for lasting appearance			
Control Options	Photocell, Motion Sensor, 1-10V Dimming			
Operating Temp	-40° to 113° F			
Rated Life	> 50,000 hrs.			



Pole Mount
Fits 2-3/8" or 3" Tenons

DIMENSION

unit: inch/mm

