

LED Area Light

Adjustable Series



WHY UPGRADE WITH EMIUM'S LED AREA LIGHTS?

Unlock the power with this high performance commercial grade LED Area Light. Features a slim design with housing completely sealed against moisture and environmental contaminants.

High energy efficiency and low cost, Suitable for mounting heights ranging from 26-50' in area light application.

FEATURES

- Reduces energy consumption and operating costs by 80% or more.
- Luxeon LEDs and Inventronics drivers
- Maintenance free operation - lasts up to 20 times longer than conventional lighting
- 150 watts or higher has built in surge suppression.
- IP66 Rating
- Estimated 100,000 hour LED lifespan.
- No UV, IR, or RF interference
- Environmentally friendly - fully recyclable
- No mercury or other hazardous material

Recommended Use:

- Auto dealerships
- Parking lots
- Walkways
- Roadways



LED Area Light

Adjustable Series

180W



300W



400W



72/108/144/180 watts
Field Selectable

- 120-277V or 347-480V
- 167lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing
Die-Cast Aluminum

- Dark Bronze - *Standard*
- White, Black, or Silver - *Custom Order*

Please see accessories page for mounting types and control options.

Options

- Optical Occupancy sensor
- Optical Photocell

EX: EL-MS-SL08-180W27V50KD

120/180/240/300 watts
Field Selectable

- 120-277V or 347-480V
- 167lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing
Die-Cast Aluminum

- Dark Bronze - *Standard*
- White, Black, or Silver - *Custom Order*

Please see accessories page for mounting types and control options.

Options

- Optical Occupancy sensor
- Optical Photocell

EX: EL-MS-SL08-300W27V40KW

300/320/360/400 watts
Field Selectable

- 120-277V or 347-480V
- 167lm/W
- 1-10V Dimming
- CCT Adjustable: 4000K/5000K

Housing
Die-Cast Aluminum



- Dark Bronze - *Standard*
- White, Black, or Silver - *Custom Order*

Please see accessories page for mounting types and control options.








Options

- Optical Occupancy sensor
- Optical Photocell

EX: EL-MS-SL08-400W27V40KW



EPA OF AREA LIGHT

| Item |  |  |  |  |  |  |  |
|----------------|---|---|---|---|--|---|---|
| | 1 | 2 @90° | 2 @120° | 2 @180° | 3 @90° | 3 @120° | 4 @90° |
| 100W/140W/180W | 0.3632 | 0.6849 | 0.8861 | 0.7264 | 1.0481 | 1.2078 | 1.0481 |
| 250W/300W/400W | 0.4758 | 0.8091 | 1.059 | 0.9516 | 1.2849 | 1.3923 | 1.2849 |

