

There is a Better Way



LED Flood Lights

Adjustable Series



WHY UPGRADE WITH EMIUM'S LED FLOOD LIGHTS?

The newest series of our LED Flood Lights aims to provide customers a product that is economical, efficient, and flexible.

The low-profile and stylish exterior design can be well integrated into various architectural environments.

At the same time, it takes into account the functions of light control, CCT & Power adjustable, which can save energy to the greatest extent and facilitate customer stocking.

FEATURES

- Durable surface coating powder spraying and fully sealed tempered glass can extend the durability of the fixture
- Optics(NEMA Type): 7H*7V
- IP65 Rating
- Estimated 50,000 hour LED lifespan.
- The heat-resistant and impact-resistant toughened glass maximizes light extraction while obtaining a great night appearance
- No mercury or other hazardous material

Recommended Use:

- Landscape
- Building facades
- Commercial lighting



LED Flood Lights

Adjustable Series





Dimensions:





6/10/12/15 watts Field Selectable

- 120-277V
- 140lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing


Die-Cast Aluminum

- Dark Bronze Standard
- White or Black Custom Order

Options

Photocell

(15W/27W)



11/15/20/27 watts Field Selectable

- 120-277V
- 133lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing

Die-Cast Aluminum

- Dark Bronze Standard
- White or Black Custom Order


Options


Photocell





Dimensions: (40W/65W)





65W



27/41/54/65 watts Field Selectable

- 120-277V
- 145lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing

Die-Cast Aluminum

- Dark Bronze Standard
- White or Black Custom Order

Options

Photocell

14/21/29/40 watts

Field Selectable

- 120-277V
- 145lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing

Die-Cast Aluminum

- Dark Bronze Standard
- White or Black Custom Order

Options

Photocell









Flood Lights

Adjustable Series





33/50/68/90 watts Field Selectable

- 120-277V
- 150lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing

Die-Cast Aluminum


- Dark Bronze Standard
- · White or Black Custom Order


Options

• Photocell

EX: EL-MS-FL-90W27VDDKD YK B77

Dimensions: (90W/120W)





120W



52/71/98/120 watts

Field Selectable

- 120-277V
- 150lm/W
- 1-10V Dimming
- CCT Adjustable: 3000K/4000K/5000K

Housing

Die-Cast Aluminum

- Dark Bronze Standard
- White or Black Custom Order

Options

Photocell

EX: EL-MS-FL-120W27VDDKB SP B77

Mounting

(90W/120W)





(90W/120W)



YOKE MOUNT

(15W/27W/40W/65W)



1/2" KNUCLE MOUNT **Standard**



TRUNNION MOUNT

POWER	■-		* *			•	
	1	2 @90°	2 @120°	2@180°	3 @90°	3 @120°	4 @90°
27W(Knuckle MNT) / ft.²	0.2891	0.3626	0.3750	0.2891	0.6517	0.6641	0.6517
65W(Knuckle MNT) / ft.²	0.4517	0.5367	0.5752	0.4517	0.9884	1.0269	0.9884
120W(Slipfitter MNT)/ft.²	0.9680	1.0876	1.4235	0.9680	2.0556	2.3915	2.0556
120W(Slipfitter MNT Facing down directly)/ft.²	0.3367	0.5689	0.7591	0.6374	0.9056	0.9910	0.9056





