



◆ **FEATURES**

- Reduce energy consumption and operating costs by more than 60%
- Models available for both vertical and horizontal mounting applications
- Maintenance free operation - lasts up to 8 times longer than most CFLs
- Superior thermal management with aluminum PCB and aluminum housings
- Cool beam - No UV or IR, reduces air conditioning loads significantly
- Environmentally friendly - fully recyclable, no mercury or other hazardous material
- 50,000 hrs. L70 rated life

LED PL Lamps

Retrofits for Fluorescent Downlights and Sconces

Replacement bulbs suitable for general lighting applications. Ideal for office common areas, museums, retail spaces, hotels, healthcare facilities, churches, government buildings, etc.

Emium products are engineered to install into existing infrastructure and fixtures, making the transition from fluorescent simple and cost-effective. Options include configurations that are compatible with existing ballasts or can operate on 120-277VAC direct line voltage.



Horizontal

Vertical

Stick – Omni-directional

5 Year Warranty



*Not all models are DLC qualified, see exceptions on back side.

for more information email info@emium.com

or call 224.735.3435 | www.emium.com



emium

emium lighting, see differently



SPECIFICATIONS

Model	EL-VL-PLS-XXW-XX		EL-VL-PLV-XXW-XX		EL-VL-PLH-XXW-XX			
Power	5W	7W	12W		5	7	12	12
Lumens	500	700	1100		500	700	1100	1100
Input Voltage	B - Direct 120-277V		A - Ballast AB - Dual Mode		B - Direct 120-277V			A - Ballast AB - Dual Mode
Base Type	GX23/G23, G24q, G24d, E26, GU24		G24q		GX23/G23, G24q, G24d, E26, GU24			G24q
Beam Angle	260°		140°					
Color Temp	2700K		3000K	3500K	4000K	5000K	6000K	
* DLC QPL	No		Yes		No			Yes - Type A
CRI	> 80							
Dimmable	No							
Suitable Location	Damp or Dry							
Life Rating	>50,000hrs							

Ordering Guide			PL (Plug-in) Lamps:		Example - EL-VL-PLH-12WA-G24q-35		
Emium Lighting	Product Code	Product Category	Application Type	Power Consumption (XX)Watts	Power Input	Base Type	CCT (X,X00) Kelvin
EL	VL	PL	H - Horizontal	12	AB - Dual Mode	G24q	27, 30, 35, 40, 50
				(5, 7, 12)	A - Ballast		
			V - Vertical	12	B - Direct 120-277V	GX23/G23, G24q, G24d, E26, GU24	
			S - Omni-directional (Stick)	(5, 7)	A - Ballast AB - Dual Mode	G24q	
					B - Direct 120-277V	GX23/G23, G24q, G24d, E26, GU24	

for more information email info@emium.com

or call 224.735.3435 | www.emium.com

