

# Linear LED High Bay

High bay fixtures for general interior lighting applications. Ideal for commercial buildings, factories, warehouses, supermarkets, etc.

Our products feature high quality components from industry leading manufacturers for superior performance and longevity.

Photometric studies and analysis show that the performance of our 110W LED high bay fixture exceeds the illumination from a 400W metal halide HID high bay...using only 25% of the energy. While our 325W version outperforms the illumination of a 1000W HID high bay...using 30% of the energy!

We carry a complete line of products to meet all types of commercial needs. Our products are engineered to install very simply and make the transition from HID or fluorescent lighting very cost-effective.

**50,000 hrs rated life**

**5 Year Warranty**



## ◆ FEATURES

- Reduce energy consumption and operating costs by 70% or more
- Maintenance free operation - lasts up to 10 to 20 times longer than conventional lighting
- No UV or IR and no RF interference
- Suitable for damp locations and can be surface mounted or suspended for maximum flexibility in numerous applications.
- Environmentally friendly - fully recyclable, no mercury or other hazardous material

**emium***emium lighting, see differently*

for more information email [info@emium.com](mailto:info@emium.com)

or call 224.735.3435 | [www.emium.com](http://www.emium.com)


**SPECIFICATIONS**

Model	EL-ZY-H2-110W-NW40	EL-ZY-H5-165W-NW40	EL-ZY-H3-225W-NW40	EL-ZY-H6-325W-NW40	
	EL-ZY-H2-110W-DW50	EL-ZY-H5-165W-DW50	EL-ZY-H3-225W-DW50	EL-ZY-H6-325W-DW50	
Power (watts)	110	165	225	325	
Lumen Output	16,406	24,563	32,000	46,361	
Efficacy	> 142 lm/watt				
Input Voltage	100-277VAC or 480VAC				
CRI	> 83 R <sub>a</sub>				
Color	5000K standard (4000K color temp available upon request)				
Dimensions	Length	24"	24"	46"	46"
	Width	12.6"	18"	12.6"	18"
	Height	4"	4"	4"	4"
Diffuser/cover	Frosted or no cover, optional wire guard (glass free)				
Operating Temperature	-30°F to 140°F				
Mounting Options	Surface mount, Pendant mount Cable or chain suspension (with v-clips for dual point)				
Suitable for damp locations	Yes				
Dimmable	Yes 0 - 10V (optional)				
Rated Life	50,000 hrs				

Pendant mount



Suspension mount



for more information email [info@emium.com](mailto:info@emium.com)  
 or call 224.735.3435 | [www.emium.com](http://www.emium.com)


**emium**
*emium lighting, see differently*